POWERKEY ULTIMATE

Learn more at www.hmisystems.net



- Increased output drive from 20mA to 100mA
- Full color LED indicators including pure white
- Standard and custom legends (no mins, no set up fees)
- Added overload feedback on output drives to detect short circuit or over current events
- Significant power reductions, PKU2400 consumes with all LED's active 250mA@12v
- Simplified CAN messaging using our CAN connect software to control multiple LED's within single message

PKU Keypad Improved Features with the Designer Firmware:


- Improved thermal dissipation
- 256 step brightness control for each color
- New LED visual effects (blink, pulse, spin ripple)
- On / Off, momentary, toggle, scroll / step functions programmable for each key
- Added overload feedback on output drives to detect short circuit or over current events
- Autonomous operation (key press causes LED to change state without feedback from external device)
- NMEA2000 bus compliant (support ISO requests, address claim, binary status 127501 and binary control 127502 messages)


PKU Keypad Protocols & Accessories:

- o RS485
- CANopen
- o J1939
- NMEA2000
- Free Software Utility
- Accesories Catalog
- Connector options include:
 - Deutsch, Molex and more



1955 West State Rd 426 | Oviedo, FL 32765 | Tel: 407.359.8171 | Fax: 407.359.8170 info@hmisystems.net | www.hmisystems.net





<u>0.62</u> 0.82

5.35

